
Tubo rigido - Seamless tube

TUBO RIGIDO - SEAMLESS PIPE

TT	TRAFILATO BONDERIZZATO *							
	Spessore Parete Tubo (mm)							
De (mm)	1	1,5	2	2,5	3	3,5	4	5
4	600							
5	450							
6	340	600	880					
8	260	430	530					
10	210	330	470	630				
12	170	260	350	500	650			
14	140	220	300	410	540			
15	130	200	280	380	500			
16	120	190	260	340	450			
18	100	170	220	280	350			
20	80	140	200	250	320		500	
22	70	130	170	210	270			
25		110	150	190	250		350	480
28	50	90	130	160	210		300	430
30		90	130	150	190		280	
35		80	100	120	150		230	320
38			80	100	140		220	320
42			80		120		180	250

TZ	TRAFILATO ZINCATO *							
	Spessore Parete Tubo (mm)							
De (mm)	1	1,5	2	2,5	3	3,5	4	5
4	600	0	0	0	0	0	0	0
6	450	0	0	0	0	0	0	0
8	340	600	880	0	0	0	0	0
10	260	430	530	0	0	0	0	0
12	210	330	470	630	0	0	0	0
14	170	260	350	500	650	0	0	0
15	140	220	300	410	540	0	0	0
16	130	200	280	380	500	0	0	0
18	120	190	260	340	450	0	0	0
20	100	170	220	280	350	0	0	0
22	80	140	200	250	320	0	500	0
25	70	130	170	210	270	0	0	0
28	0	110	150	190	250	0	350	480
30	50	90	130	160	210	0	300	430
35	0	90	130	150	190	0	280	0
38	0	80	100	120	150	0	230	320
42	0	0	80	100	140	0	220	320

* max pressione di esercizio – max working pressure

